



## BLX C BL 250W24VDCD SB8OBH 5-7K 2CBABK

BLX™ C LED BOWLIGHT is designed to improve the ability to see during navigation and maneuvering at night. By combining the proven technology of the BLX™ Series with practical testing of the optical features, the end result is a powerful bowlight that will increase safety and endure in very harsh environments.

|              |               |
|--------------|---------------|
| Item Number  | LNL0333-1     |
| GTIN         | 7072720000649 |
| Stock status | A             |



### Technical specifications

#### Electrical Data

|                       |   |
|-----------------------|---|
| EMC Category          | EMC1 : EMC B – IEC 60533 Bridge and Open deck |
| Main Feed DC (V)      | 22  |
| Min                   |   |
| Main Feed DC (V)      | 30  |
| Max                   |   |
| Total consumption (W) | 250   |

#### Optic

|       |   |
|-------|---|
| Optic | SB8-OBH - Spot Beam 8° and Oval Beam horizontal |
|-------|---|

#### Special

|                 |     |
|-----------------|-----|
| 1 Lux Range (m) | 527 |
|-----------------|-----|

#### Certificates

|                 |      |
|-----------------|------|
| Certification   | DNV  |
| Marine Approved | true |

#### Technical Data

|                                  |       |
|----------------------------------|-------|
| Minimum ambient temperature (°C) | -40   |
| Maximum ambient temperature (°C) | 55    |
| IP classification                | 66/67 |
| Corrosion class                  | C5-M  |

#### Light Technical Data

|                            |        |
|----------------------------|--------|
| Light source               | LED    |
| Lumen out (lm)             | 21010  |
| Lumen per Watt (lm/W)      | 84     |
| Lamp colour temp (K)       | 5000   |
| CRI Colour rendering index | >70    |
| Candela Output (cd)        | 278000 |
| Light source included      | true   |
| Dimmable                   | true   |

#### Housing

|                           |                              |
|---------------------------|------------------------------|
| Main body material        | Seawater-resistant aluminium |
| Surface treatment         | Anodized                     |
| Body colour               | BL - Black                   |
| Main body colour name     | Graphite black               |
| Main body colour surface  | Powder coated                |
| Main body colour RAL code | RAL 9011                     |
| Mounting bracket material | Stainless steel AISI 316     |

#### Dimensions

|                 |          |
|-----------------|----------|
| Length (mm)     | 310      |
| Width (mm)      | 280      |
| Height (mm)     | 160      |
| Net weight (kg) | 5.700044 |

#### Cable Inlet

|                         |                         |
|-------------------------|-------------------------|
| Cable gland             | M20-Nickel plated brass |
| Number of cable glands  | 2                       |
| Number of blind plugs   | 0                       |
| Max cable diameter (mm) | 13                      |
| Min cable diameter (mm) | 7                       |

**Logistic Data**

|                        |        |
|------------------------|--------|
| Item gross weight (kg) | 6.1957 |
|------------------------|--------|

## Images

