



## 1nm Comb Sidelight, upside-down w/FB base

101-003-FB-REVERSE

1nm Comb Sidelight, upside-down w/FB base  
Horizontally mounted with 2,5m cable

Specifications	
Number	101-003-FB-REVERSE
Light Color	Red,Green
Dimensions metric	Ø92,5mm x 36mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Support</a>
Intensity	NULL
Dimensions imperial	Ø3.6" x 1.4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light,Installation guide,precabled with 2.5 meter shielded marine grade cable
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438042629
IP rating	IP68
Power draw (W)	1,4
UPC Code	879343042752
Connection	2.5m cable

**Specifications**

**Current consumption (mA @ 12VDC)** 87

**Current consumption (mA @ 24VDC)** 48

**Vessel size** Under 12M

**Min. feed wire gauge** 0.5mm<sup>2</sup> AWG22

**Weight (Kg)** 0.55 Kg

**Weight (Oz)** 19.32 Oz