## LOPOLIGHT



## 1nm Comb Sidelight, silver w/FB base

## 101-003-FB

1nm Comb Sidelight, silver w/FB base Horizontally mounted with 2,5m cable

Specifications	
Number	101-003-FB
Light Color	Red,Green
Dimensions metric	Ø92,5mm x 58mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <u>www.lopolight.com under</u> <u>Support</u>
Intensity	NULL
Dimensions imperial	Ø3.6" x 1.4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light,Installation guide,precabled with 2.5 meter shielded marine grade cable
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438042605
IP rating	IP68
Power draw (W)	1,4
UPC Code	879343042738
Connection	2.5m cable

## LOPOLIGHT

Specifications	
Current consumption (mA @ 12VDC)	87
Current consumption (mA @ 24VDC)	48
Vessel size	Under 12M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.55 Kg
Weight (Oz)	19.32 Oz