



2nm 360° White, black anodized

200-012G2-PRO

2nm 360° white, black anodized
 Horizontally mounted on POM base (IP68)
 Cable direction side
 incl. HDPE base plate
 Quality cable glands - 2 sizes included:
 7-13mm (1/4"-1/2") cable diameter
 4.5-10mm (5/32"-3/8") cable diameter

Specifications	
Number	200-012G2-PRO
Light Color	White
Dimensions metric	Ø92,5mm x 75mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 2.9"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012073
IP rating	IP68
Power draw (W)	2,6
UPC Code	879343012076
Connection	Plug connector

Specifications	
Current consumption (mA @ 12VDC)	167
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	110
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	1 Kg
Weight (Oz)	35.27 Oz