



2nm 360° Red, black anodized

200-014G2-B 2,5M

2nm 360° Red, black anodized, w/2,5m cables
Horizontally mounted with 2,5m cable

Specifications

Number	200-014G2-B 2,5M
Light Color	Red
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438020672
IP rating	IP68
Power draw (W)	2,1
UPC Code	879343020804
Connection	2.5m cable

Specifications

Current consumption 150
(mA @ 12VDC)

Stock status Not usually in stock

Current consumption 85
(mA @ 24VDC)

Vessel size Under 12M,12-20M,20-50M

Min. feed wire gauge 0.5mm² AWG22

Weight (Kg) 0.6 Kg

Weight (Oz) 21.16 Oz