



2nm Tri-color/anchor, black w/FB base

201-007-FB-B

For sailing yachts up to 20 meters
Horizontally mounted with 0,7m cable
FB (flat base) POM mounting system

Specifications	
Number	201-007-FB-B
Dimensions metric	Ø92,5mm x 36mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com/underSupport
Dimensions imperial	Ø3.6" x 1.4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438044340
IP rating	IP68
Power draw (W)	2.6
UPC Code	879343044473
Connection	0.7m cable
Current consumption (mA @ 12VDC)	150
Current consumption (mA @ 24VDC)	81
Min. feed wire gauge	0.5mm ² AWG22

Specifications	
Weight (Kg)	0.72 Kg
Weight (Oz)	25.39 Oz