



2nm Tricolor, Anchor w/Strobe, black anodized

201-007S-B TB

Horizontally mounted on POM base
The base is IP68 waterproof
Includes cable gland for 4-14mm cable with connector.

Specifications	
Number	201-007S-B TB
Dimensions metric	Ø92,5mm x 36mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Dimensions imperial	Ø3.6" x 1.4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438044258
IP rating	IP68
Power draw (W)	2.6
UPC Code	879343044381
Connection	0.7m cable
Current consumption (mA @ 12VDC)	150
Current consumption (mA @ 24VDC)	81
Min. feed wire gauge	0.5mm2 AWG22

Specifications	
Weight (Kg)	0.92 Kg
Weight (Oz)	32.36 Oz