



3nm Masthead, black anodized w/FB base

201-011KL-FB-B

3nm Masthead, black anodized w/FB base
Horizontal mounted with 0.75m cable

Specifications	
Number	201-011KL-FB-B
Light Color	White
Dimensions metric	Ø92,5mm x 36mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Dimensions imperial	Ø3.6" x 1.4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light,Installation guide,precabled with 0.75 meter shielded marine grade cable
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438043411
IP rating	IP68
Power draw (W)	2
UPC Code	879343043544
Connection	0.7m cable
Current consumption (mA @ 12VDC)	137

Specifications

**Current consumption
(mA @ 24VDC)** 80

Vessel size Under 12M

Min. feed wire gauge 0.5mm² AWG22

Weight (Kg) 0.48 Kg

Weight (Oz) 16.92 Oz