



3nm Masthead, Double, black anodized

201-011KLST-PRO

3nm dbl masthead, black anodized., 0.75m
Horizontally mounted on POM base (IP68)
Cable direction side
incl. HDPE base plate
Quality cable glands - 2 sizes included:
7-13mm (1/4"-1/2") cable diameter
4.5-10mm (5/32"-3/8") cable diameter

Specifications	
Number	201-011KLST-PRO
Light Color	White
Dimensions metric	Ø92,5mm x 96,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>15cd
Dimensions imperial	Ø3.6" x 3.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012646
IP rating	IP68
Power draw (W)	3
UPC Code	879343012649
Connection	Plug connector

Specifications

**Current consumption
(mA @ 12VDC)** 232

Stock status Usually in stock

**Current consumption
(mA @ 24VDC)** 127

Vessel size 12-20M

Min. feed wire gauge 0.5mm² AWG22

Weight (Kg) 1.36 Kg

Weight (Oz) 47.97 Oz