



3nm Masthead, silver anodized

201-011

3nm masthead, silver anodized
Vertically mounted with 0,75m cable

Specifications

Number	201-011
Light Color	White
Dimensions metric	74,55 x 28 x 73,16
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>15cd
Dimensions imperial	2.9" x 1.1" x 2.88"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438009707
IP rating	IP68
Power draw (W)	3
UPC Code	879343009700
Connection	0.7m cable

Specifications

**Current consumption
(mA @ 12VDC)** 232

Stock status Usually in stock

**Current consumption
(mA @ 24VDC)** 127

Vessel size 12-20M

Min. feed wire gauge 0.5mm² AWG22

Weight (Kg) 0.43 Kg

Weight (Oz) 15.17 Oz