



2nm 360° Red, silver w/FB base

201-014-FB

2nm 360° Red, silver w/FB base

Horizontally mounted with 0,7m cable

FB (flat base) POM mounting system

Specifications

Number	201-014-FB
Light Color	Red
Dimensions metric	Ø92,5mm x 36mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under <u>Support</u>
Dimensions imperial	Ø3.6" x 1.4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light, Installation guide, pre cables with 0.75 meter shielded marine grade cable
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438042971
IP rating	IP68
Power draw (W)	2,1
UPC Code	879343043100
Connection	0.7m cable
Current consumption (mA @ 12VDC)	150

Specifications

Current consumption 85
(mA @ 24VDC)

Vessel size Under 12M,12-20M,20-50M

Min. feed wire gauge 0.5mm² AWG22

Weight (Kg) 0.45 Kg

Weight (Oz) 15.93 Oz