



## 2nm 360° Green, black w/FB base

201-015-FB-B

2nm 360° Green, black w/FB base  
Horizontally mounted with 0,7m cable  
FB (flat base) POM mounting system

Specifications	
<b>Number</b>	201-015-FB-B
<b>Light Color</b>	Green
<b>Dimensions metric</b>	Ø92,5mm x 36mm
<b>Certification</b>	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Support</a>
<b>Dimensions imperial</b>	Ø3.6" x 1.4"
<b>Approved to</b>	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
<b>Visibility</b>	2nm
<b>Included In Package</b>	1 Navigation light, Installation guide, pre cables with 0.75 meter shielded marine grade cable
<b>Operating temperature</b>	-25°C to 55°C
<b>Mounting</b>	Horizontal
<b>Materials</b>	Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
<b>Operating Voltage</b>	10-32VDC
<b>EAN</b>	5704438043145
<b>IP rating</b>	IP68
<b>Power draw (W)</b>	2,1
<b>UPC Code</b>	879343043278
<b>Connection</b>	0.7m cable
<b>Current consumption (mA @ 12VDC)</b>	150

## Specifications

**Current consumption** 85  
(mA @ 24VDC)

**Vessel size** Under 12M,12-20M,20-50M

**Min. feed wire gauge** 0.5mm<sup>2</sup> AWG22

**Weight (Kg)** 0 Kg

**Weight (Oz)** 0.00 Oz