



5nm Masthead, Ice-class, black anodized

300-036-PRO-I

5nm Masthead, black anodized.
Built-in De-icing function
Horizontally mounted on POM base (IP68)
Cable direction side
incl.HDPE base plate
Quality cable glands - 2 sizes included:
7-13mm (1/4"-1/2") cable diameter
4.5-10mm (5/32"-3/8") cable diameter

Specifications	
Number	300-036-PRO-I
Light Color	White
Dimensions metric	Ø92,5mm x 111,8mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>52cd
Dimensions imperial	Ø3.6" x 4.4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Operating temperature	-60°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438011304
IP rating	IP68
Power draw (W)	7
UPC Code	879343011307
Connection	Plug connector
Current consumption (mA @ 12VDC)	0

Specifications

Stock status	Made to order
--------------	---------------

Current consumption (mA @ 24VDC)	290
-------------------------------------	-----

Vessel size	20-50M
-------------	--------

Min. feed wire gauge	1.5mm2 AWG18
----------------------	--------------

Weight (Kg)	1.34 Kg
-------------	---------

Weight (Oz)	47.26 Oz
-------------	----------