




5nm Masthead, black anodized

300-037-B

5 nm Masthead (blk), vert CB mnt, 0.7m
Vertically mounted with 0,75m cable.

Specifications	
Number	300-037-B
Light Color	White
Dimensions metric	107 x 92,5 x 74
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>52cd
Dimensions imperial	4.2" x 3.6" x 2.9"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438003330
IP rating	IP68
Power draw (W)	7
UPC Code	879343003333
Connection	0.7m cable
Current consumption (mA @ 12VDC)	0

Specifications

Stock status	Made to order
--------------	---------------

Current consumption (mA @ 24VDC)	290
-------------------------------------	-----

Vessel size	20-50M
-------------	--------

Min. feed wire gauge	0.5mm2 AWG22
----------------------	--------------

Weight (Kg)	1.06 Kg
-------------	---------

Weight (Oz)	37.39 Oz
-------------	----------