



6nm Masthead, Double, black anodized

300-138-PRO

6nm dbl masthead, black anodized.
Horizontally mounted on POM base (IP68)
Cable direction side
incl. HDPE base plate
Quality cable glands
7-13mm (9/32"- 1/2") cable diameter

Specifications	
Number	300-138-PRO
Light Color	White
Dimensions metric	Ø92,5mm x 143mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>94cd
Dimensions imperial	Ø3.6" x 5.6"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	6nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438004221
IP rating	IP68
Power draw (W)	13
UPC Code	879343004224
Connection	Plug connector
Current consumption (mA @ 12VDC)	0

Specifications

Current consumption (mA @ 24VDC)	580
---	-----

Vessel size	Over 50M
--------------------	----------

Min. feed wire gauge	0.5mm ² AWG22
-----------------------------	--------------------------

Weight (Kg)	1.75 Kg
--------------------	---------

Weight (Oz)	61.72 Oz
--------------------	----------