



2nm stern, silver w/FB base

301-005-FB

2nm stern, silver w/FB base

Horizontally mounted with 2,5m cable

Specifications

Number 301-005-FB

Light Color White

Dimensions metric Ø92,5mm x 36mm

Certification This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under [Support](#)

Dimensions imperial Ø3.6" x 1.4"

Approved to COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR

Visibility 2nm

Included In Package 1 Navigation light,Installation guide,precabled with 2.5 meter shielded marine grade cable

Operating temperature -25°C to 55°C

Mounting Horizontal

Materials Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane

Operating Voltage 10-32VDC

EAN 5704438043602

IP rating IP68

Power draw (W) 1,3

UPC Code 879343043735

Connection 2.5m cable

Current consumption (mA @ 12VDC) 110

Specifications

**Current consumption
(mA @ 24VDC)** 50

Vessel size Under 12M,12-20M,20-50M

Min. feed wire gauge 0.5mm² AWG22

Weight (Kg) 0.57 Kg

Weight (Oz) 19.98 Oz