



## 2nm dbl stern light, black anodized

### 301-005ST-PRO

This LED Navigation light, is our Professional Seri

Horizontally mounted on POM base (IP68)

Cable direction side

incl.HDPE base plate

Quality cable glands - 2 sizes included:...

7-13mm (1/4"-1/2") cable diameter

4.5-10mm (5/32"-3/8") cable diameter

Specifications	
Number	301-005ST-PRO
Light Color	White
Dimensions metric	Ø92,5mm x 96,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 3.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012875
IP rating	IP68
Power draw (W)	1,3
UPC Code	879343012878
Connection	Plug connector

## Specifications

**Current consumption  
(mA @ 12VDC)** 110

**Stock status** Made to order

**Lead time** 2-3 weeks

**Current consumption  
(mA @ 24VDC)** 50

**Vessel size** Under 12M,12-20M,20-50M

**Min. feed wire gauge** 0.5mm2 AWG22

**Weight (Kg)** 1.41 Kg

**Weight (Oz)** 49.73 Oz