



2nm starboard, double, black anodized

301-008ST-PRO

This LED Navigation light, is our Professional Series for commercial vessels. The PRO-Serie have the best technology available and impressive robustness, made with a thicker and harder anodizing. All the certification approvals needed for this type o

Horizontally mounted on POM base (IP68)

Cable direction side

incl.HDPE base plate

Quality cable glands - 2 sizes included:...

7-13mm (1/4"-1/2") cable diameter

4.5-10mm (5/32"-3/8") cable diameter

Specifications	
Number	301-008ST-PRO
Light Color	Green
Dimensions metric	Ø92,5mm x 96,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 3.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012950
IP rating	IP68
Power draw (W)	1,4
UPC Code	879343012953
Connection	Plug connector

Specifications

**Current consumption
(mA @ 12VDC)** 110

Stock status Usually in stock

Lead time 2-3 weeks

**Current consumption
(mA @ 24VDC)** 60

Vessel size 12-20M,20-50M

Min. feed wire gauge 0.5mm2 AWG22

Weight (Kg) 1.41 Kg

Weight (Oz) 49.73 Oz