



## 2nm 112,5° Red, Port, black anodized

### 301-009-PRO

This LED Navigation light, is our Professional Series for commercial vessels. The PRO-Serie have the best technology available and impressive robustness, made with a thicker and harder anodizing. All the certification approvals needed for this type o

Horizontally mounted on POM base (IP68)

Cable direction side

incl. HDPE base plate

Quality cable glands

7-13mm (9/32"- 1/2") cable diameter

#### Specifications

**Number** 301-009-PRO

**Light Color** Red

**Dimensions metric** Ø92,5mm x 74,5mm

**Certification** This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on [www.lopolight.com](http://www.lopolight.com) under [Support](#)

**Intensity** >5.4cd

**Dimensions imperial** Ø3.6" x 2.9"

**Approved to** COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR

**Visibility** 2nm

**Included In Package** 1 Navigation light,2 Mounting screws (M6 \* 8 mm),Installation guide

**Operating temperature** -25°C to 55°C

**Mounting** Horizontal

**Materials** Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane

**Operating Voltage** 10-32VDC

**EAN** 5704438013001

**IP rating** IP68

**Power draw (W)** 1,2

**UPC Code** 879343013004

**Connection** Plug connector

| Specifications                   |                  |
|----------------------------------|------------------|
| Current consumption (mA @ 12VDC) | 90               |
| Stock status                     | Usually in stock |
| Lead time                        | 1-2 weeks        |
| Current consumption (mA @ 24VDC) | 50               |
| Vessel size                      | 12-20M,20-50M    |
| Min. feed wire gauge             | 0.5mm2 AWG22     |
| Weight (Kg)                      | 1.04 Kg          |
| Weight (Oz)                      | 36.68 Oz         |