



2nm 112,5° Red, port, dbl, black Ex 1&2 ice-class

301-009ST-PRO-I-EX

2nm port, double, black EX Zone 1&2 ice-class
 Certified for use in ATEX Zone 1 & 2
 Built-in De-icing function
 Horizontally mounted on 400-037 EX/MIL alu base
 Cable direction side, incl. HDPE base plate.
 No Cable glands or Ground strap included.

Specifications	
Number	301-009ST-PRO-I-EX
Light Color	Red
Dimensions metric	Ø92,5mm x 125,5mm
Certification	This Navigation Light is certified by DNV, Dancert (Approved to: Ex mb eb IIB T5 Gb) and ExVeritas (PQAN/UKQAN/QAR), the Declaration of conformity and the certificates can be found on https://lopolight.com/support
Dimensions imperial	Ø3.6" x 4.9"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,BV,RINA,LR,MCA,ATEX 2014/34/EU,IEC 60079-0/7/18,UK Ex
Visibility	2nm
Included In Package	1 Navigation light,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438040588
IP rating	IP68
Power draw (W)	1
UPC Code	879343040710
Connection	Plug connector
Current consumption (mA @ 12VDC)	92

Specifications	
Special Attributes	IceClass,EX,ATEX
Current consumption (mA @ 24VDC)	56
Vessel size	12-20M,20-50M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	1.4 Kg
Weight (Oz)	49.38 Oz