



2nm double port, black anodized

301-009ST-PRO

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.

Horizontally mounted on POM base (IP68)
Cable direction side
incl.HDPE base plate
Quality cable glands - 2 sizes included:....
7-13mm (1/4"-1/2") cable diameter
4.5-10mm (5/32"-3/8") cable diameter

Specifications	
Number	301-009ST-PRO
Light Color	Red
Dimensions metric	Ø92,5mm x 96,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 3.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438013032
IP rating	IP68
Power draw (W)	1,2
UPC Code	879343013035
Connection	Plug connector

Specifications

Current consumption (mA @ 12VDC)	90
----------------------------------	----

Stock status	Made to order
--------------	---------------

Lead time	4-6 weeks
-----------	-----------

Current consumption (mA @ 24VDC)	50
----------------------------------	----

Vessel size	12-20M,20-50M
-------------	---------------

Min. feed wire gauge	0.5mm2 AWG22
----------------------	--------------

Weight (Kg)	1.41 Kg
-------------	---------

Weight (Oz)	49.73 Oz
-------------	----------