



## 3nm Starboard, black anodized.

### 301-108-PRO-I

3nm stbd, black anodized.  
 Built-in De-icing function  
 Horizontally mounted on 400-037 POM base (IP68)  
 Cable direction side  
 incl. HDPE base plate  
 Quality cable glands  
 7-13mm (9/32"- 1/2") cable diameter

Specifications	
Number	301-108-PRO-I
Light Color	Green
Dimensions metric	Ø92,5mm x 103,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under Support
Intensity	>15cd
Dimensions imperial	Ø3.6" x 4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-60°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438014336
IP rating	IP68
Power draw (W)	2,6
UPC Code	879343014339
Connection	Plug connector

## Specifications

**Current consumption  
(mA @ 12VDC)** 183

**Stock status** Made to order

**Current consumption  
(mA @ 24VDC)** 110

**Vessel size** Over 50M

**Min. feed wire gauge** 1.5mm2 AWG18

**Weight (Kg)** 1.2 Kg

**Weight (Oz)** 42.32 Oz