



3nm port, black anodized.

301-109-PRO-I

3nm port, black anodized.
 Built-in De-icing function
 Horizontally monted on 400-037 POM base (IP68)
 Cable direction side
 incl. HDPE base plate
 Quality cable glands
 7-13mm (9/32"- 1/2") cable diameter

| Specifications | |
|-----------------------|--|
| Number | 301-109-PRO-I |
| Light Color | Red |
| Dimensions metric | Ø92,5mm x 103,5mm |
| Certification | This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopelight.com under Support |
| Intensity | >15cd |
| Dimensions imperial | Ø3.6" x 4" |
| Approved to | COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR |
| Visibility | 3nm |
| Included In Package | 1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide |
| Operating temperature | -60°C to 55°C |
| Mounting | Horizontal |
| Materials | Black hard coat anodized aluminum 50μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane |
| Operating Voltage | 20-32VDC |
| EAN | 5704438014190 |
| IP rating | IP68 |
| Power draw (W) | 2,2 |
| UPC Code | 879343014193 |
| Connection | Plug connector |

Specifications

| | |
|---|-----|
| Current consumption (mA @ 12VDC) | 153 |
|---|-----|

| | |
|---------------------|---------------|
| Stock status | Made to order |
|---------------------|---------------|

| | |
|---|----|
| Current consumption (mA @ 24VDC) | 92 |
|---|----|

| | |
|--------------------|----------|
| Vessel size | Over 50M |
|--------------------|----------|

| | |
|-----------------------------|--------------|
| Min. feed wire gauge | 1.5mm2 AWG18 |
|-----------------------------|--------------|

| | |
|--------------------|--------|
| Weight (Kg) | 0.8 Kg |
|--------------------|--------|

| | |
|--------------------|----------|
| Weight (Oz) | 28.22 Oz |
|--------------------|----------|