



3nm 112,5° Red, port, black anodized.

301-109-PRO

3nm port, black anodized.
Horizontally mounted on 400-037 POM base (IP68)
Cable direction side
incl. HDPE base plate
Quality cable glands
7-13mm (9/32"- 1/2") cable diameter

Specifications	
Number	301-109-PRO
Light Color	Red
Dimensions metric	Ø92,5mm x 103,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>15cd
Dimensions imperial	Ø3.6" x 4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438014206
IP rating	IP68
Power draw (W)	2,2
UPC Code	879343014209
Connection	Plug connector

Specifications	
Current consumption (mA @ 12VDC)	153
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	92
Vessel size	Over 50M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	1.09 Kg
Weight (Oz)	38.44 Oz