



SL40 R5 SH470 230V 2000W CF

The SL40 R5 is designed with a IP56 rating and is approved for temperatures down to -40°C and up to +50°C. Seawater resistant aluminum housing and motor house, coupled with excellent heat management, ensures a searchlight with long run-time and long lifetime. THIS ITEM IS DELIVERED WITH PANEL AND FOCUS.

Item Number	500107241
GTIN	7070404033297
Stock status	M



Technical specifications

Navigation

Operation mode	Remote R5
PAN Sector	360
TILT Sector	55
Focus	Electronic
1 Lux Range	2366

Certificates

Marine Approved	True
-----------------	------

Technical Data

Minimum ambient temperature (°C)	-40
Maximum ambient temperature (°C)	50
IP classification	56

Light Technical Data

Light source	QT
Number of lamps	1
Lumen value supplied light source (lm)	50000
Candela Output (cd)	5600000
Light source included	True

Electrical Data

Minimum Voltage -10% (VAC)	230
Maximum voltage +10% (VAC)	230
Minimum frequency -5% (Hz)	50
Maximum frequency +5% (Hz)	60

Optic

Material of diffuser	Tempered glass
Colour of reflector	Silver
Material of reflector	Glass

Housing

Main body material	Seawater-resistant aluminium
Body colour	White
Main body colour name	White

Dimensions

Length (mm)	360
Width (mm)	615
Height (mm)	1040
Diameter (mm)	525
Net weight (kg)	58.88

Logistic Data

Net weight (kg)	58.88
-----------------	-------

Illustrations

